

Blum Clip Top 120°

For standard applications with convenient opening angle for Blum Aventos HF



5

Blum Concealed Hinges



- > Material: Steel cup and hinge arm
- > Finish: Nickel plated
- > Installation: Door to cabinet without tools (clip system)
- > Adjustment facility: Side adjustment from -2 to +2 mm, depth adjustment from -2 to +3 mm, height adjustment max. ±3 mm depending on the mounting plate
- > Without automatic closing spring (for use with Tip-On door catch)
- > Suitable for Blumotion soft closing mechanism for clip fixing
- > Not compatible with Clip Top Blumotion 110°

Minimum gap for doors with chamfered edges (r = 1 mm) with factory settings

Door thickness mm	Distance to cup E mm			
	3.0	4.0	5.0	6.0
16	0.9	0.9	0.9	0.9
18	1.4	1.4	1.4	1.3
19	1.7	1.6	1.6	1.5
20	2.0	1.9	1.9	1.8
21	2.4	2.4	2.2	2.1
22	2.7	2.6	2.5	2.4
24	4.0	3.7	3.6	3.4
26-32	Trial mounting is recommended			
Minimum gap F				

→ Full overlay mounting

Door overlay mm													
5	6	7	8	9	10	11	12	13	14	15	16	17	
									3	4	5	6	0
						3	4	5	6				3
			3	4	5	6							6
3	4	5	6										9
Distance to cup E mm							Mounting plate distance mm						

Cup fixing	Model	Cat. No.
Without tools (Inserta)	70T5590BTL	342.81.060
For screw fixing	70T5550.TL	342.81.400

Packing: 50 pieces

Drilling pattern/technical information	► MB 5.63
Mounting plates and accessories	► MB 5.100
Blumotion soft closing system for doors	► MB 5.108